



GT03A

Magnetic GPS Tracker

-  **GPS+AGPS+LBS positioning**
-  **Vibration and movement alert**
-  **2500/5000mAh battery**
-  **Geo-fence alarm**
-  **Voice monitor**
-  **IP65 dust and waterproof**
-  **Powerful magnet**
-  **Tracked by: SMS, APP, Web**

GSM / GPS Specification

GSM frequency	850/900/1800/1900 MHz	
GPRS	Class 12, TCP/IP	
Memory	32+32Mb	
Phrase error	RMSPE<5, PPE<20	
Max output	GSM850/GSM900:33±3dBm	GSM1800/GSM1900:30±3dBm
Max frequency error	±0.1ppm	
GPS chipset	MTK high sensitivity chip	
Frequency	L1, 1575.42MHz C/A code	
GPS channel	66	
Location accuracy	<10 meters	
Tracking sensitivity	-165dBm	
Acquisition sensitivity	-148dBm	

Function & Package

Voice monitor range	≤5 meters	
Dust-waterproof level	IP65	
Button	1xPower On/Off	
Working voltage/current	3.7VDC/60mA	
Charger voltage/current	5VDC/1A	
Operating temperature	-20℃~70℃	
Battery	2500mAh/3.7V	5000mAh/3.7V
Dimension	91.5(L)*57.0(W)*24(H)mm	91.5(L)*57.0(W)*37.5(H)mm
Weight	100g	202g

